

## DH-SD6580/6581-HN

### 1.3Megapixel HD Network PTZ Dome Camera



**DH-SD6580-HN:** 18x optical zoom, 1.3M CCD, 12/15fps@1.3M, 25/30fps@720P, IP67, Dahua HD Block Camera

**DH-SD6581-HN:** 18x optical zoom, 1.3M CCD, 12/15fps@1.3M, 25/30fps@720P, IP67, Hitachi HD Block Camera

## Features

### Camera & Video

- 1/3" 1.3Megapixel SONY Progressive Scan CCD
- Powerful 18x optical zoom and 12x digital zoom
- H.264 & Dual-stream video encoding and JPEG image capture
- 12/15fps@1.3M(1280×960) & 25/30fps@720P resolution
- Day/Night(ICR), Auto iris, Auto focus, AWB, BLC
- Up to 24 privacy masking areas
- Built-in Web server, NVR, CMS(PSS/DSS) & DMSS

### Dome Drive

- Max 400 °/s pan speed, 360° continuous pan rotation & auto flip with no blind spot monitor
- Up to 255 preset, 5 auto scan, 8 tour, 5 pattern
- Auto recognition of general protocols such as DH-SD, Pelco-P/D, and etc
- Speed setup according to the focal distance, auto rotation speed adjust in accordance with the lens zoom rate
- Auto restore to previous PTZ and lens status after power failure
- Time Task: Auto activation of Preset/Scan/Tour/ Pattern by preset-time

## DH-SD6580/6581-HN

- Idle Motion: Call preset/tour and etc operations after idle for the specified time (including the idle status after the system boots up)
- OSD and operation prompts of various languages
- Build-in 7/2 channel alarm input/output
- Intelligent 3D positioning function
- IP67 all-environments protection, 4000V thunder-proof, auto constant temperature & anti-fog
- Easy installation with user-friendly designs

### Specifications


Model	DH-SD6580-HN	DH-SD6581-HN
<b>Camera</b>		
Image Sensor	1/3" 1.3M Progressive Scan CCD	
Effective Pixels	1296(H) x 966(V)	
Lens	18x optical zoom	
	f=4.5mm(Wide)~81mm(Tele), F1.6~F2.7	f=4.7mm(Wide)~84.6mm(Tele), F1.6~F2.8
Digital Zoom	12x	
Horizontal Viewing Angle	51.6°(Wide)~3.1°(Tele)	55.2°(Wide)~3.2°(Tele)
Min. Object Distance	10mm(wide) ~ 1000mm(Tele)	
Min. Illumination	0.1Lux/F1.6(Color), 0.01Lux/F1.6(B/W)	0.5Lux/F1.6(Color), 0.02Lux/F1.6(B/W)
Electronic Shutter	NTSC:1/4~1/10000s, PAL:1/3~1/10000s, 20level	
White Balance	Auto/ATW/Indoor/Outdoor/Manual	
BLC	ON/OFF	
WDR	/	ON/OFF
Day/Night	Auto(ICR) / Color / B/W	
S/N Ratio	More than 50 dB	
Privacy Masking	ON/OFF (up to 24 privacy masking areas)	
Analog Video Output	BNC(1.0Vp-p / 75Ω), PAL / NTSC	
<b>Video &amp; Audio</b>		
Video Compression	H.264 / MPEG4	
Image Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×128)	
Encoding Speed	Main Stream	PAL: 1.3M(1~12fps), 720P(1~25fps)
		NTSC: 1.3M(1~15fps), 720P(1~30fps)
	Extra Stream	PAL: D1/CIF/QCIF (1~25fps)
		NTSC: D1/CIF/QCIF (1~30fps)
Bit Rate	32K~8Mbps	
Audio Compression	G.711a(32Kbps) / AMR(10.2Kbps)	
Audio Mode	Off/Audio input/Audio output	
<b>Dome Drive</b>		
Pan/Tilt Range	Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor	
Manual Control Speed	Horizontal: 0.1°~300°/s, Vertical: 0.1°~150°/s	
Preset Speed	Horizontal: 400°/s, Vertical: 180°/s	

## DH-SD6580/6581-HN

Preset	255
PTZ Mode	5 Auto Pattern, 8 Auto Tour, 5 auto scan
3D Positioning	Yes
Speed Setup	Human-oriented focal Length/ speed adaptation
Info Display	Time, Location, Dome title, Dome coordinates, Temperature, Alarm, and etc.
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate preset/scan/tour/ patter if there is no command in the specified period.
Time Task	Auto activation of Preset/Scan/Tour/ Pattern by preset-time
Alarm	7/2 alarm input/output, Triggering Preset/Tour/Pattern/Scan//Alarm output
Protocol	DH-SD, Pelco-P/D, Auto recognition of general protocols
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Network Functions	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server
Max Remote Users	20 Users simultaneously
Processor	TI DaVinci Series DSP
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, remote operation & local recording
Remote Operation	Monitor, PTZ control, Voice Intercom, System setting, Playback, File download, Log information, Maintenance & Upgrade
Local Recording	SD/SDHC, Max 32GB
User Interface	WEB, CMS(DSS/ PSS), DMSS, NVR
<b>General</b>	
Power Supply	AC 24V/3A(±10%)
Power Consumption	12W(Indoor), 50W(Outdoor, heater on)
Working Temperature	-40°C ~ 60°C
Working Humidity	<90%
Protection Level	IP67, 4000V thunder, surge and wave protection
Dimension	Φ222(mm) x 322(mm)
Weight	5.0kg

## DH-SD6580/6581-HN

### Dimensions (mm)



#### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: [overseas@dahuatech.com](mailto:overseas@dahuatech.com)

[www.dahuatech.com](http://www.dahuatech.com)

\*Design and specifications are subject to change without notice.

© 2011 Dahua Technology Co., Ltd.